



ALFAGLOS® GLAZING POLYESTER PUTTY



Description ▼

Alfaglos® Glazing is a BPO 2-component polyester body filler that contains premium materials to achieve a fine result and is very easy to sand. It provides a superior adhesion to various substrates along with excellent physical characteristic resulting in easy application on both small and large areas.

Properties ▼

- Excellent adhesion to bare steel and other substrates
- Easy and fast filling
- Fine homogenous structure
- Easy sanding
- Excellent flexibility

Substrates ▼

- Steel
- Fiberglass
- OEM finishes
- 2 K primers
- Aluminum
- Galvanized steel
- Properly treated old painted surfaces

Recoatability ▼

- Alfaglos® Epoxy Filler
- Alfaglos® Polyurethane Filler

Surface Preparation ▼

- **Steel :**
 - Sand surface using no. 3 sand paper.
 - Clean surface from dirt, dust and oil.
- **Existing Finishes :**
 - Sand surface using P-150 sand paper.
 - Clean surface from dirt, dust and oil.
- **Polyester surface or 2 K primer :**
 - Sand surface using P-180 sand paper.
 - Clean surface from dirt, dust and oil.

Product Preparation ▼

● Mixing Ratio	Base : Hardener = 100 : 2 – 3 by weight
● Hardener Type	BPO
● Tools	Mixing board, filler knife, plastic or rubber spreader
● Application	Apply on substrate immediately after mixing with hardener to avoid air bubbles.
● Pot Life	± 4 minutes
● Drying time at 25°C Touch dry	Touch Dry : ± 20 minutes Sanding Interval : 25 - 30 minutes

Packaging ▼

Putty	Metal Can
Hardener	Plastic tube

Color ▼

Putty	White
Hardener	Red

Storage ▼

Store in a dry area at 50-70 % RH with temperature of 20-30 °C
Shelf Life at 25°C : 12 Months from date of manufacture and in original sealed container

Remarks ▼

- Do not use polyester putty on unsanded substrates
- Use the hardener according to the amount recommended to get the optimal application
- Do not apply top coat directly over polyester putty to avoid absorption
- Material has to be at room temperature before use