TECHNICAL DATA SHEET

PT. ALFATAMA INTICIPTA-INDONESIA

MIDAS® POLYESTER PUTTY



Description

Midas® Polyester Putty is a premium quality putty formulated with polyester resin. This putty is easy to apply, easy to sand, and features excellent adhesion, ensuring a high-quality and durable paint finish.

Properties

- Excellent adhesion to bare steel and other substrates
- Easy to sand
- Easy and fast filling
- Easy to apply
- Flexible
- Strong and durable

Substrates

- Steel
- Fiberglass
- OEM Finishes
- 2 K primers
- Aluminum
- Galvanized steel
- Properly treated old painted surfaces

Recoatability

 Alfaglos® Epoxy Filler	 Alfaglos® Polyurethane Filler

Surface Preparation

- **Steel :**
  Sand surface using no. 3 sand paper. Clean surface from dirt, dust and oil.
- **Cat Lama :**
  Sand surface using no. 150 sand paper. Clean surface from dirt, dust and oil.
- **Polyester surface or 2 K primer :**
  Sand surface using no. 180 sand paper. Clean surface from dirt, dust and oil.

PT. Alfatama Inticipta
Jl. Raya Semarang Demak Km 12.7 Loireng Sayung, Kab Demak
59563, Indonesia
+ 6224 76452841 / +6224 76450841
Info.center@alfatama.com

Product Preparation

Mixing Ratio	Base : Hardener = 100 : 1 – 2 by weight
Hardener Type	CHPO
Tools	Mixing board, filler knife, plastic or rubber spreader
Application	Apply on substrate immediately after mixing with hardener to avoid air bubbles.
Pot Life	± 3 minutes
Drying time at 25°C Touch dry Sanding interval	 ± 12 minutes 20-25 minutes

Packaging

Putty	Metal Can
Hardener	Plastic Tube

Color

Putty	Green
Hardener	Yellow

Storage

Store in a dry area at 50-70 % RH with temperature of 20-30°C
Shelf Life at 25°C : 12 Months from date of manufacture and in original sealed container

Remarks

- Do not use polyester putty on unsanded substrates.
- Use the hardener according to the amount recommended to get the optimal application.
- Do not apply top coat directly over polyester putty to avoid absorption
- Material has to be at room temperature before use.

PT. Alfatama Inticipta
Jl. Raya Semarang Demak Km 12.7 Loireng Sayung, Kab Demak
59563, Indonesia
+ 6224 76452841 / +6224 76450841
Info.center@alfatama.com